

# Empowering your eyes with seamless vision experience!

## Private Label Opportunities (OEM)

We offer dry contact lens manufacturing services, as well as finished product contact lenses, allowing you to launch your own brand of high quality contact lenses with ease and confidence.

We are committed to assisting you in creating bespoke contact lenses that align perfectly with your brand's vision and values.

## About Our Company

SuperVision Optimax (SVO) is a contact lens manufacturer dedicated to producing high quality soft contact lenses.

Our skilled team combines technical expertise with advanced technologies to produce exceptional contact lenses that deliver all-day comfort and clarity.

### Contact us at:

☎ +6012 282 2778

✉ [info@supervision.com.my](mailto:info@supervision.com.my)

📍 Lot 38, Putra Industrial Park,  
40160 Sungai Buloh,  
Selangor, Malaysia

🌐 <https://supervision.com.my>



**SUPERVISION**



## SOFT CONTACT LENSES

[WWW.SUPERVISION.COM.MY](http://WWW.SUPERVISION.COM.MY)



## Cast Moulding

Our contact lenses are made using automated cast moulding technology, which delivers high precision and consistent quality in every contact lens.

Each contact lens is carefully manufactured to meet rigorous quality standards, ensuring a comfortable fit and excellent visual performance.



# Lens FEATURES



## MPC Technology



to improve biocompatibility, all-day comfort, and long-lasting hydration while preventing lipid and protein deposition.

## Aspheric Design

for crystal-clear HD vision throughout your entire field of vision.




## Tapered Edge

for a no-slip fit that allows your eyes breathe every time you blink.

## UV Protection

Class II UV blocker to shield against 87% of UVA and 97% of UVB radiation.



## ASPHERIC

### PC-58

Lens Material	HEMA – MPC
Water Content	58%
Diameter	14.20 mm
Base Curve	8.60 mm
Centre Thickness	0.070 mm (@ -3.00D)
UV Blocker	Yes
Power Range	-0.50D to -6.00D (in 0.25D steps) -6.50D to -10.00D (in 0.50D steps) +0.50D to +4.00D (in 0.25D steps) +4.50D to +6.00D (in 0.50D steps)

### PC-55

Lens Material	HEMA – MPC
Water Content	55%
Diameter	14.20 mm
Base Curve	8.60 mm
Centre Thickness	0.070 mm (@ -3.00D)
UV Blocker	Yes
Power Range	-0.50D to -6.00D (in 0.25D steps) -6.50D to -10.00D (in 0.50D steps) +0.50D to +4.00D (in 0.25D steps) +4.50D to +6.00D (in 0.50D steps)