

Anping Redstar Wire Mesh MFG Co., LTD



About REDSTAR





> 30 Years history

> 52,000m2 Production Area

▶ 18 Patent Certificates

> 300 Employees

5 Business Divisions

REDSTAR Main Markets:

■ U.S.A. ■ Canada ■ Australia ■ Europe





About REDSTAR







REDSTAR Screens





PRODUCTS RANGE

- Woven Wire Screen
- Wire / Poly Ripple
- ●PU Screens
- ●PU Customized Products






REDSTAR Screens – Wire/Poly Ripple




Self Cleaning Screens


Type W



Type T



Type D



Capacity

Range of Wire Dia. 1.60 mm – 9.00 mm

Range of Aperture 2.50 mm – 45.00 mm



REDSTAR Self-cleaning Screen



Tensioned- Self-cleaning Screen



Range:

- 1. Wire dia. 1.37-9.19 mm
- 2. Aperture 2.03-40 mm

Material:

- 1. . Patented wire
- 2. Satainless wire (304,316,316L etc)



REDSTAR Self-cleaning Screen



Modular- Self-cleaning Screen



Range:

- 1. Wire dia. 1.37-9.19 mm
- 2. Aperture 2.03-40 mm

Material:

- 1. .Patented wire
- 2. .Satainless wire (304,316,316L etc)



REDSTAR Self-cleaning Screen



Modular- Self-cleaning Screen



Range:

- 1. Wire dia. 1.37-9.19 mm
- 2. Aperture 2.03-40 mm

Material:

- 1. .Patented wire
- 2. .Satainless wire (304,316,316L etc)





REDSTAR Screens – Wire/Poly Ripple



Self Cleaning Screens



Type D, Trellstep fastening system



Type D, Pin & Sleeve





TSO STOREGISTION TO STOREGISTI

Increase up to 48% efficiency

Before Change Red Star selfcleaning Screen










REDSTAR Screens – wire screens



Woven Wire Screens



Capacity	
Range of Wire Dia.	0.90 mm – 19.05 mm
Range of Aperture	0.90 mm – 157.00 mm
Dies. Available	Over 1200pcs
Min. Leading Time	10 days / container



REDSTAR Screens – wire screens




Woven Wire Screens

Flat Top 101.6mm Apt. 19.05mm W.D.



Double Wire 76.2mm Apt. 6.35mm W.D.





Fine Mesh

REDSTAR PU Fine Screens









Usually being used on DERRICK high-frequency vibrating screens

Available for Selecting ■ Hardness 80 – 87 ShA ■ Thickness 5 – 7 mm ■ Resilience 45% - 47% ■ Aperture Type Slot ■ Aperture Size 0.075 / 0.1 / 0.12 / 0.15 / 0.18







PU Fine Screen Mesh
Panels' Size: 1045 X 700, 840X1245, 1000X2320, 1200X2320
Opening
0.063
0.075
0.1
0.12
0.15
0.18
0.20
0.23
0.25
0.30
0.35
0.40
0.50
0.60
0.70
0.80
0.85
1.00
1.20
1.50


Note, the specification with red color is in stock normally.





REDSTAR Screens - PU





Modular, Pebble Stones



Wedge Panel, Coal Ore



Cross Tension, Basalt



PU Fine Mesh, Derrick




Flip Flow, Bivitec



REDSTAR Screens - PU





Modular Panel, dual hardness



Modular Panel, self cleaning



REDSTAR- PU Solutions




Bolts Protector



PU Capping



Declogging Rods



Spray Nozzle



PU Screening Solution

REDSTAR are capable of supporting our clients with a variety of customized PU solution, helping increase the screening performance



REDSTAR- PU Solutions



PU Wearing Plates



PU Impeller



PU Wearing Solution

REDSTAR are also capable of supporting our clients with a variety of customized PU solution, helping increase plant productivity & lower operation cost per ton




REDSTAR Partners



N 400		
> 120	Database of	four main partners
/ 120	Dutubuse of	odi illalli partificio

- > 70 Countries our main partners from
- > 15 Longest Years of non-stop partnership
- > 12 Top Screening Machine Manufacturers, like
- ➤ 13 Top Screen Media Manufacturers, like













REDSTAR Quality

DELIVERY

AFTER-SALES SERVICE







Continuously qualified for ISO 9001 audit, ensure the consistence of high quality only for 30 years





Parameter	Redstar		ASTM E2016-15		DIN47833		GB/T 13307	
	Range	Value	Range	Value	Range	Value	Range	Value
Aperture Tolerance %	≤152.4	±3%	≤3.2	6%		±5%		
		±3%	≤4.8	5%		±5%		
		±3%	≤6.4	5%		±5%		
		±3%	≤9.5	4%		±5%		
		±3%	≤12.7	3%		±5%	55 < w≤125	4.5%
		±3%	≤19.1	3%		±5%	16 < w≤55	5%
		±3%	≤25.4	3%		±5%	10 < w≤16	5.6%
		±3%	≤38.1	3%		±5%	5.6 < w≤10	6.3%
		±3%	≤76.2	2%		±5%	4 < w≤5.5	7%
		±3%	≤127	2%		±5%	2 < w≤4	7%
	≥2.38	±3%	≤177.8	2%		±5%	1< w≤2	7%
	≤19.05	±0.03	≥12.7	0.08	< 15	0.090	YBT 5103	
	12.5	±0.03	≥2.03	0.05	< 10	0.070	>10.00	0.07
Wire Dia.	≥1.37	±0.03	≥0.89	0.03	< 8.5	0.060	>6.00~10.00	0.06
Tolerance mm					< 5.6	0.045	>4.00~6.00	0.05
					< 3.2	0.035	>2.6~4.00	0.04
					< 1.5	0.025	≤2.60	0.03
Diagnoline	< 2 m	≤9mm	N/A			10 mm / m	N/A	•
	≥2 m	≤12mm						
Width mm		± 5	N/A			10 mm / m	N/A	
Length mm		± 3	N/A			10 mm / m	1000 < b≤2000	\pm (3+d)

High standard of products ensures all the products to fulfill the quality standard for any customer from any market







▲ Raw Material Test

SGS approval is required before acceptance



▲ Internal Inspection

Sample for approval prior massive production







▲ Professional Production Tech.

Ensure the quality standard fulfillment






▲ Experienced Personnel

Ensuring the delivery of high quality products







▲ Trackable Quality Control System

27 inspection process minimize the products defects before delivery



▲ Continuous Improvement on Quality

Dedicated for slef-improving on quality always








▲ PU Raw Material

From well known brands only



▲ Internal QC

Testing on each batch to ensure the quality compliance for all raw materials



▲ Formula Design

Based on industrial experience, specific formula would be designed as per product specifications, to achieve suitable hardness, rupture strength, wear resistance & resilience

PREPARATIONS BEFORE PRODUCTION








PRODUCTION & QC

SINCE 1989








▲ Storage

Products being neat & clean before final delivery to our clients



▲ Packing

Customized packing enable safe delivery & convenience receipt of goods by our clients








▲ Storage

Dust-free workshop, ensuring products being neat & clean before final delivery to our clients




▲ Packing

Customized packing enable convenience receipt of goods by our clients

DELIVERY









▲ Final Inspection

Final inspection by third party or customer personally, are always welcome anytime.









▲ 19 Woven Wire Screen Equipments

▲ Over 660 Crimping Wheels

Production Facilities