

Skates Fixed Type AS Series

- To be used heavy objects while its moving, which makes the Movement much more easier,
- Use heavy duty sealed bearings to spread around the loading and ensure the ease of movements.
- Use best Nylon or Polyurethane wheels to Protect the floors from damage.
- The skate roller is maintenance-free and can be fitted with handles for carrying.
- Platform with rubber surface help stability and supplies the protection for the object loaded.



Model		AS20-N		AS40-N		AS60-N		AS120-N	
		AS20-P		AS40-P		AS60-P		AS120-P	
Capacity	kg/lps	2000	4400	4000	8800	6000	13200	12000	26400
Load wheels	pcs	2pcs Nylon/Pu		4pcs Nylon/Pu		6pcs Nylon/Pu		8pcs Nylon/Pu	
Wheel size	mm/inch	ø82 x 100	ø3-1/4" x 3-15/16"	ø82 x 100	ø3-1/4" x3-15/16"	ø82 x 100	ø3-1/4" x 3-15/16"	ø115 x 60	ø4-1/2" x 2-3/8"
Skate size	mm/inch	115 x 270 x 110	4-1/2" x 10-5/8" x 4-5/16"	230 x 270 x 110	9" x 10-5/8" x 4-5/16"	345 x 270 x 110	13-9/16" x 10-5/8" x 4-5/16"	400 x 345 x 145	15-3/4" x 13-9/16" x 5-11/16"
Weight	kg/lbs	7.5	17	kg	37	25	55	40	88

* AS=Adjustable Skate N=Nylon P=Polyurethane NA/PA=Built-up Available.

Stearable Skates SS Series

- They incorporate a drawbar and a platform that swivel on a thrust bearing allowing movement around bends.
- The steerable skates can balance by itself and walk on an even keel on uneven ground.
- Power coated give a high quality durable finish.

PROFESSIONAL CLASS



Model		SS40-N		SS60-N		SS240-N	
		SS40-P		SS60-P		SS240-P	
Capacity	kg/lps	4000	8800	6000	13200	12000	26400
Load wheels	pcs	4pcs Nylon/Pu		8pcs Nylon/Pu		16pcs Nylon/Pu	
Wheel size	mm/inch	ø82 x 100	ø3-1/4" x 3-15/16"	ø82 x 100	ø3-1/4" x 3-15/16"	ø115 x 60	ø4-1/2" x 2-3/8"
Skate size	mm/inch	150 x 310 x 110	9-13/16" x 12-3/16" x 4-5/16"	560 x 395 x 110	22" x 15-9/16" x 4-5/16"	1120 x 415 x 145	44-1/16" x 16-5/16" x 5-11/16"
Weight	kg/lbs	16	35	50	110	160	352

* SS=Steerable Skate N=Nylon P=Polyurethane NA/PA= Built-up Available.

Marketed by



FABTEX ENGINEERING WORKS

240/7, Irugur Road, Chinniyampalayam (Po),
Coimbatore - 641 062.

Fac : 0422-2625465, Off : 0422-2580844

Cell : 94432 81802

E-mail : fabtexind@yahoo.co.in

Web : www.fabtexengg.com