

Certificate of Compliance

Certificate Number:

UL-US-L354137-92406102-3

Report Reference:

E354137-20160429

Issue Date:

2024-03-14

Issued to:

BLUEVIEW ELEC-OPTIC TECH CO LTD
1000 SECTION 2, 2ND KONGGANG RD
SOUTHWEST AVIATION INDUSTRIAL
DEVELOPMENT ZONE SHUANGLIU CHENGDU, Sichuan Sheng
610207
China

This certificate confirms that representative samples of:

IFDR - Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 2108, Edition 2, Issue Date 2015-12-07, Revision Date 2023-04-18

Additional Information:

See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



UL Mark Certification Program Manager



Certificate number UL-US-L354137-92406102-3

Report reference E354137-20160429

Date 2024-03-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BV-FLEX-AI-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-Al-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-AO-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-AO-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BI-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BI-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BO-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BO-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-DI-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-I-5V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-O-5V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEXCC-BI-24V-X, Where "X" can be any	Low Voltage LED Surface-Mounted Light
alphanumeric characters represents LED color.	
BV-FLEXCC-BO-24V-X, Where "X" can be any	Low Voltage LED Surface-Mounted Light
alphanumeric characters represents LED color.	
BV-HPB-L-Y-X, where L can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents bar length, Y can be any	
alphanumeric character represents LED quantity, X can be	
any alphanumeric characters represents LED color	
BV-LT9-L-Y-X, where L can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents bar length, Y can be any	
alphanumeric character represents LED quantity, X can be	
any alphanumeric characters represents LED color	
BV-SFLEX-I-12-X, WHERE "X" CAN BE ANY	Low Voltage LED Surface-Mounted Light
ALPHANUMERIC CHARACTERS REPRESENTS LED	
COLOR.	

David Piecuch

UL Mark Certification Program Manager



Certificate number UL-US-L354137-92406102-3

Report reference E354137-20160429

Date 2024-03-14

BV-SFLEX-I-24V-X, Where "X" can be any alphanumeric characters represents LED color.	Low Voltage LED Surface-Mounted Light
BV-SFLEX-O-12V-X, Where "X" can be any alphanumeric characters represents LED color.	Low Voltage LED Surface-Mounted Light
BV-SFLEX-O-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
N24A-X, Where "X" can be any alphanumeric characters represents LED color.	Low Voltage LED Surface-Mounted Light

David Piecuch

UL Mark Certification Program Manager





Certificate of Compliance

Certificate Number:

UL-CA-L354137-92406102-3

Report Reference:

E354137-20160429

Issue Date:

2024-03-14

Issued to:

BLUEVIEW ELEC-OPTIC TECH CO LTD
1000 SECTION 2, 2ND KONGGANG RD
SOUTHWEST AVIATION INDUSTRIAL
DEVELOPMENT ZONE SHUANGLIU CHENGDU, Sichuan Sheng
610207
China

This certificate confirms that representative samples of:

IFDR7 - Low-voltage Lighting Systems, Power Units, Luminaires and Fittings Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

CSA C22.2 NO. 250.2, 1st Ed., Issue Date: 2020-01-01

Additional Information:

See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



UL Mark Certification Program Manager



Certificate number UL-CA-L354137-92406102-3

Report reference E354137-20160429

Date 2024-03-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
BV-FLEX-AI-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-Al-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-AO-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-AO-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BI-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BI-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BO-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-BO-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-DI-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-I-5V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEX-O-5V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-FLEXCC-BI-24V-X, Where "X" can be any	Low Voltage LED Surface-Mounted Light
alphanumeric characters represents LED color.	
BV-FLEXCC-BO-24V-X, Where "X" can be any	Low Voltage LED Surface-Mounted Light
alphanumeric characters represents LED color.	
BV-HPB-L-Y-X, where L can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents bar length, Y can be any	
alphanumeric character represents LED quantity, X can be	
any alphanumeric characters represents LED color	
BV-LT9-L-Y-X, where L can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents bar length, Y can be any	
alphanumeric character represents LED quantity, X can be	
any alphanumeric characters represents LED color	
BV-SFLEX-I-12-X, WHERE "X" CAN BE ANY	Low Voltage LED Surface-Mounted Light
ALPHANUMERIC CHARACTERS REPRESENTS LED	
COLOR.	



UL Mark Certification Program Manager



Certificate number UL-CA-L354137-92406102-3

Report reference E354137-20160429

Date 2024-03-14

BV-SFLEX-I-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-SFLEX-O-12V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	
BV-SFLEX-O-24V-X, Where "X" can be any alphanumeric	Low Voltage LED Surface-Mounted Light
characters represents LED color.	_
N24A-X, Where "X" can be any alphanumeric characters	Low Voltage LED Surface-Mounted Light
represents LED color.	_

David Piecuch

UL Mark Certification Program Manager

