

SFS-PLUS LUG



VT107

SFS-PLUS RIB



VT108

SFS-119



VT119

LUG



VT101 VT122

RIB



VT102C VT103C VT104C

RIB



VT113 VT114 VT115 VT116 VT121

EXTRA LOAD TIRE

 **Vee Rubber**

COMB



VT106 VT112

LIGHT TRUCK



VT141 VT173

SAFARI



VT111



VT215

SNOW



VT105

MUD + SNOW



VT110

EXTRA LOAD TIRE

VT 101 LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.00-13	8	4.5	175	658	675	640	60	60
6.00-14	6	4.5	172	683	610	580	46	46
	8	4.5	172	683	710	675	60	60
	10	4.5	172	683	810	760	75	75
6.50-14	8	4.5	183	699	795	755	60	60
7.00-15	12	5.5	201	756	1150	1093	84	84
	14	5.5	201	756	1270	1207	99	99
7.00-16	12	5.5	205	800	1170	1115	82	82
	14	5.5	205	800	1265	1200	93	93
7.50-15	12	6	228	790	1315	1250	85	85
	14	6	228	790	1415	1345	99	99
7.50-16	10	6	208	811	1265	1200	75	75
	12	6	208	811	1370	1305	85	85
	14	6	208	811	1475	1405	96	96
8.25-16	14	6.5	241	982	1630	1550	85	85
	16	6.5	241	982	1760	1670	95	95
8.25-20	14	6.5	241	982	2180	1950	96	96
9.00-20	14	7	255	1025	2300	2185	96	96
10.00-20	16	7.5	274	1060	2760	2485	105	105
11.00-20	16	8	290	1092	2900	2610	105	105
12.00-20	18	8.5	320	1130	3170	3015	114	114
12.00-24	18	8.5	309	1231	4000	3650	112	112

EXTRA LOAD



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	183	699	910	865	75	75
7.50-16	16	6	208	811	1580	1500	107	107
9.00-20	16	7	255	1025	2455	2330	107	107
10.00-20	18	7.5	274	1060	3095	2790	114	114
11.00-20	18	8	290	1092	3130	2975	114	114



VT 102

RIB

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.00-13	8	4.5	169	637	675	640	60	60
6.00-14	6	4.5	173	684	610	580	46	46
	8	4.5	173	684	710	675	60	60
6.50-14	8	4.5	183	699	795	755	60	60
6.50-16	8	4.5	180	761	870	825	60	60
	10	4.5	180	761	960	915	70	70
	12	4.5	180	761	1050	995	82	82
7.00-15	10	5.5	204	774	1030	980	71	71
	12	5.5	204	774	1150	1095	85	85
7.00-16	10	5.5	204	790	1075	1020	71	71
	12	5.5	204	790	1170	1115	82	82
	14	5.5	204	790	1265	1200	93	93
7.50-15	12	6	220	784	1315	1250	85	85
	14	6	220	784	1415	1345	99	99
7.50-16	10	6	220	811	1265	1200	75	75
	12	6	220	811	1370	1305	85	85
	14	6	220	811	1475	1405	96	96
8.25-20	14	6.5	238	986	2180	1950	96	96
	16	6.5	238	986	2033	1931	103	103

EXTRA LOAD



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	183	699	910	865	75	75

VT 103C

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	16	8	302	1095	2900	2610	105	105

EXTRA LOAD



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	18	8	302	1095	3130	2975	114	114

VT 104C

TRAILER



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	275	1057	2760	2485	105	105

VT 105

MUD & SNOW



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	8	4.5	188	719	795	755	60	60

EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	188	719	910	865	75	75



VT 106

COMB

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	10	6	202	792	1265	1200	75	75
	12	6	202	792	1370	1305	85	85
	14	6	202	792	1475	1405	96	96

VT 107

SFS-PLUS



EXTRA LOAD **SUPER 5 STARS** **PLUS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	16	6	224	836	1580	1500	107	107
9.00-20	16	7	262	1026	2455	2332	107	107
10.00-20	16	7.5	280	1083	2760	2485	105	105
	18	7.5	280	1083	3095	2790	114	114
11.00-20	16	8	300	1113	2900	2610	105	105
	18	8	300	1113	3095	2790	114	114
	20	8	300	1113	3130	2975	114	114
12.00-20	20	8.5	344	1157	3375	3206	135	135

VT 108

SFS-PLUS



EXTRA LOAD **SUPER 5 STARS** **PLUS**

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	265	1028	2455	2330	107	107
10.00-20	18	7.5	288	1053	3095	2790	114	114
11.00-20	18	8	305	1112	3130	2975	114	114

VT 112

COMB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
8.25-20	14	6.5	233	987	2180	1950	96	96
	16	6.5	233	987	2033	1931	103	103

VT 113

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	14	7	258	1024	2300	2185	96	96
10.00-20	16	7.5	277	1060	2760	2485	105	105

EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	258	1024	2455	2330	107	107
10.00-20	18	7.5	277	1060	3095	2790	114	114

VT 114

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
12.00-20	18	8.5	317	1125	3170	3015	114	114

VT 115

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	16	8	297	1097	2900	2610	105	105

EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
11.00-20	18	8	297	1097	3130	2975	114	114

VT 116

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
8.25-16	14	6.5	225	847	1630	1550	85	85
	16	6.5	225	847	1760	1670	95	95

VT 119

EXTRA LOAD

SUPER 5 STARS

PLUS



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
9.00-20	16	7	262	1045	2455	2330	107	107

VT 121

RIB



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAID)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	276	1055	2760	2485	105	105

VT 122

LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAID)	
					SINGLE	DUAL	SINGLE	DUAL
10.00-20	16	7.5	277	1058	2760	2485	105	105



VT 110 M+S MUD & SNOW

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.50-16	14	6	232	837	1475	1405	96	96



VT 111 SAFARI

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	8	4.5	189	703	795	755	60	60

EXTRA LOAD

SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	189	703	910	865	75	75

VT 127

SEMI-LUG



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
7.00-15	8	5.5	205	763	935	888	60	60
12.00-24	18	8.5	321	1251	4000	3650	112	112

VT 141

SMALL LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-10	8	3.5	144	514	295	280	51	51
5.00-12	8	3.5	148	566	485	460	56	56

VT 173

SMALL LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-12	8	3.5	137	558	485	460	56	56

VT 215

LIGHT TRUCK



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
5.00-12	10	3.5	144	569	555	525	71	71
6.50-14	8	4.5	190	711	795	755	60	60

EXTRA LOAD



SIZE	PLY RATING	STANDARD RIM (INCH)	SECTION WIDTH(MM.)	OVERALL DIMETER(MM.)	MAXIMUM LOAD (KG.)		INFLATION PRESSURE (PAI)	
					SINGLE	DUAL	SINGLE	DUAL
6.50-14	10	4.5	190	711	910	865	75	75